



Engine Oils

Hydraulic Oils

Lube Oils

FilClean™ OFC

Oil Flushing and Transfer Cart

HIGH FLOW OIL FILTER AND TRANSFER CART!

The MSC FilClean OFC is a high flow lube and hydraulics oil filtering, flushing and transfer cart designed for use on large oil volumes with a maximum viscosity limit of 1000 cSt depending on flow.


It uses customer specified high capacity, high efficiency hydraulic filter elements and has available flows of 25, 50 and 100 gpm.

It comes standard on a powder coated portable durable steel cart but can also be permanently mounted for continuous filtration of your oil.

- LUBE OILS
- ENGINE OILS
- HYDRAULIC OILS



FEATURES



1. HEAVY DUTY LOCKING CASTERS
2. OPTIONAL POWERCORD AND CUSTOMER SPECIFIED 3 PHASE PLUG
3. PANEL MOUNTED INDICATOR GAUGES
4. VARIETY OF FILTER MANUFACTURERS AND MICRON RATINGS TO CHOOSE FROM
5. DURABLE 25 OR 50 GPM PROGRESSIVE CAVITY OR 100 GPM STEEL GEAR PUMP
6. OPTIONAL 2" SUPERFLEX HYDRAULIC INLET AND OUTLET HOSES WITH 2" ISOLATION VALVES
7. CONTROL PANEL WITH ELECTRICAL INTERLOCK, FILTER PLUGGED, OVER PRESSURE AUTO OFF, PUMP RUNNING INDICATOR LIGHTS.
8. HOSE AND POWER CORD HOLDERS
9. STEEL PUSH HANDLE
10. POWDER COATED STEEL FRAME WITH DRIP TRAY.

FCOFC- TABLE 1 - TABLE 2 - TABLE 3 - TABLE 4 - TABLE 5

FLOW VOLTAGE FILTER MOUNT ADDER

Table 1: Flow

25	25 GPM (MSC PSK Progressive Cavity Pump Standard)
50	50 GPM (MSC PSK Progressive Cavity Pump Standard)
100	100 GPM (Gear Pump)

Note: PSK Pump Max Upstream Pressure 60 PSIG
Gear Pump Max Upstream Pressure 100 PSIG

Table 2: Voltage

BLANK	460/360 Standard
SV	Special Custom Voltage (Discuss with MSC)

Table 3: Filter Manufacturer

DM	MSC Dome Filter 36" Housing *
HYP	Hypro LF Housing **
PLL	Pall 610 40" Athalon Housing ***
SFIL	Special Filter - Discuss With MSC

Note: Specify Micron Rating Next To Chosen Manufacturer

- * MSC 2.5, 3, 6, 12, 25 (Beta 1000) Dual Phase Microglass
- ** HYP .5, 1, 3, 6, 10, 16, 25 (Beta 1000) Dual Microglass
- *** PLL 3, 5, 7, 12, 25 (Beta 2000) Athalon Element

Table 4: Mounting

CP	Portable Cart
CS	Permanent Skid

Table 5: Adders - see note

Blank	No Adders
SFH	Super Flex 2" Hydraulic Hose JIC Fittings - See Note
IV	2" Isolation Valves Inlet/Outlet
SA	Special Customer Requested Adder (Contact MSC)

Note: Specify Length of Hose next to SFH in Feet.

Specifications

Flow/Max Outlet Pressure

25 gpm/60 psig
50 gpm/60 psig
100 gpm/100 psig

Electrical

460/60/3 - FLA < 5 A


Weight & Dimensions

Weight 500-600 Lbs Depending on Adders
Dimensions: 36" W x 48" L x 60" Aprox

Oil Viscosity Limit

25 GPM - 1000 cSt
50-100 GPM - 500 cSt

Standard Control Box Includes



MSC FILTRATION TECHNOLOGIES

Corporate Offices & Distribution Center

MSC Filtration Technologies
198 Freshwater Blvd.
Enfield, Connecticut 06082
Ph: 800-237-7359 | (860)745-7475
Fax: (860) 745-7477

Email: sales@mscfiltrertech.com
Web: www.mscfiltrertech.com