

VAC-U-MAX

Distributed By:
 MSC Filtration Technologies 198 Freshwater Blvd Enfield, CT 06082
 Phone: 860-745-7475 | Fax: 860-745-7477 | Email: sales@mscfiltertech.com | Web: www.mscfiltertech.com

Model TK Liquid Recovery/ Transfer Tank Kit Unit



PERFECT FOR:

- Parts washers
- Machine tool sumps
- Drum to drum transfer
- Sludge removal from finishing tanks
- Ink wells on printing presses
- Liquid spill cleaning including flammable liquids
- Hazardous liquids
- Spill kits
- Hydraulic fluids
- Transformer oil
- Wet dust collector sumps

For use with 55 gallon (minimum 18 gauge) steel close top drums. Shown above an optional VAC-U-MAX 55 gallon close top drum.



Easily fits the .75" opening on close top drum.



Equipped with a 1.5" or 2.0" inlet designed to fit a 2"npt bung on close top drum.

VAC-U-MAX

Distributed By:
 MSC Filtration Technologies 198 Freshwater Blvd Enfield, CT 06082
 Phone: 860-745-7475 | Fax: 860-745-7477 | Email: sales@mscfiltertech.com | Web: www.mscfiltertech.com

Model TK Liquid Recovery/ Transfer Tank Kit Unit



STANDARD EQUIPMENT:

- Vacuum power head with:
- Single venturi power unit
 - Noise muffler and guard for sound levels below 80 DBA
 - Manual HP air control valve
 - Adjustable orifice assembly for vacuum control 8" Hg - 16" Hg.
 - Gasketed flange for insertion in drum vent
 - Material inlet elbow
 - AutoVac liquid cutoff

**Unique design results in 99% filled drums.
 Fewer drums = Lower shipping cost!!!**

TECHNICAL DATA:

- * Single venturi power unit
- Maximum suction power 16" Hg. (208" H₂O)
 - Maximum air flow 100 SCFM
 - Suction connection 1 1/2" or 2.0"
 - Air operated, requires 35 SCFM @ 60 PSI compressed air
 - Compressed air connection 1/2" NPT (female)
 - Noise Level 79 DBA @ 6" Hg.
 - Weight 36 lbs.

Model #	Inlet Size	Material of Construction	Finish
TK-01	1.5"	CARBON STEEL	POWDER COAT
TK-02	2.0"	CARBON STEEL	POWDER COAT
TK-05	1.5"	STAINLESS STEEL	BEAD BLAST
TK-06	2.0"	STAINLESS STEEL	BEAD BLAST